
POST sipnatprefixtable id - sipnatprefix id

REST API Method: POST

[/rest/sipnatprefixtable/{identifier}/sipnatprefix/{identifier}](#)

Modifies a SIP Qualified NAT Prefix Table Entry given a specific Table Entry ID in a given [SIP Qualified NAT Prefix Table](#).

URL:

<https://192.168.0.111/rest/sipnatprefixtable/{identifier}/sipnatprefix/{identifier}>

HTTP Method

POST

Requires Authentication:

true

Parameters

| Parameter Name | Required | Service Affecting | Data Type | Default Value | Possible Values | Description |
|----------------|----------|-------------------|-----------|---------------|-----------------|---|
| Description | No | No | string | none | 64 - Max Length | A user friendly description of the prefix entry. |
| IPAddress | Yes | No | string | none | 16 - Max Length | The IP Address component of the prefix. This combined with the Netmask will be used to match against incoming SIP Via IPs and determine if the peer endpoint is behind a NAT. |
| Netmask | Yes | No | string | none | 16 - Max Length | The Netmask component of the prefix. This combined with the IP Address will be used to match against incoming SIP Via IPs and determine if the peer endpoint is behind a NAT. |



Helpful Tip

The POST can contain either only the attributes that are being updated, or the full set of attributes for the resource