
PUT remotelog id

REST API Method: **PUT** /rest/remotelog/{identifier}

Creates a Remote Log Configuration Table given a specific Table ID.

URL:

https://192.168.0.111/rest/remotelog/{identifier}

HTTP Method

PUT

Requires Authentication:

true

Parameters

| Parameter Name | Required | Service Affecting | Data Type | Default Value | Possible Values | Description |
|----------------|----------|-------------------|-----------|---------------|--|---|
| ConfigIEState | No | Yes | Enum | 1 | Possible values: <ul style="list-style-type: none">0 - esDISABLED1 - esENABLED | Specifies the Administrative State of the resource. |
| DefaultLevel | Yes | No | Enum | 4 | Possible values: <ul style="list-style-type: none">0 - IIDefault1 - IITrace2 - IIDebug3 - IIInfo4 - IIWarn5 - IIError6 - IIFatal7 - IIOff | Controls the default minimum severity level of messages sent to this server. This default value can be overridden on a per-system basis via the Subsystems Configuration . Informational will produce the most output, and Fatal will produce the least. {note}Trace and Debug are not allowed to be set for the global log level. |

| | | | | | | |
|------------------------|-----|----|--------|------|--|---|
| SyslogFacility | Yes | No | Enum | 9 | <p>Possible values:</p> <ul style="list-style-type: none"> • 0 - sfUser • 1 - sfKern • 2 - sfMail • 3 - sfDaemon • 4 - sfAuth • 5 - sfLpr • 6 - sfNews • 7 - sfUucp • 8 - sfCron • 9 - sfLocal0 • 10 - sfLocal1 • 11 - sfLocal2 • 12 - sfLocal3 • 13 - sfLocal4 • 14 - sfLocal5 • 15 - sfLocal6 • 16 - sfLocal7 | Controls which Syslog Facility will be used when sending log entries. This can be used to facilitate the sorting of messages from different nodes on a central Syslog server. |
| ServerAddress | Yes | No | string | none | 128 - Max Length | Specifies the IP address or FQDN of the Syslog server where log entries will be sent. |
| ServerPort | Yes | No | int | 514 | <p>Possible values:</p> <ul style="list-style-type: none"> • 514 - Minimum • 65534 - Maximum | Specifies the Syslog server port number where log entries will be sent. |
| ServerTransport | Yes | No | Enum | 0 | <p>Possible values:</p> <ul style="list-style-type: none"> • 0 - stUDP • 1 - stTCP | Specifies the protocol to be used for sending log entries to the Syslog server. |