

POST sipsg id

REST API Method: **POST** /rest/sipsg/{identifier}

Modifies a SIP Signaling Group Table given a specific Table ID.



Note

The SIP Signaling Group identifier can only be within the range 1-10000 (inclusive)

URL:

https://192.168.0.111/rest/sipsg/{identifier}

HTTP Method

POST

Requires Authentication:

true

Parameters

Parameter Name	Required	Service Affecting	Data Type	Default Value	Possible Values
customAdminState	Yes	Yes	Enum	1	Possible values: <ul style="list-style-type: none">0 - cmCustomDisal1 - cmCustomEnat2 - cmCustomDrair
Description	Yes	No	string	none	64 - Max Length
ProfileID	Yes	No	int	1	Possible values: <ul style="list-style-type: none">1 - Minimum65534 - Maximum
Channels	Yes	Yes	int	10	Possible values: <ul style="list-style-type: none">1 - Minimum960 - Maximum

ServerSelection	No	No	Enum	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - eSelectionRoun • 1 - eSelectionPriot • 2 - eSelectionFirst/ • 3 - eSelectionDnsS • 4 - eSelectionRegis
ServerClusterId	No	No	int	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
RelOnQckConnect	Yes	No	Enum	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
RelOnQckConnectTimer	No	No	int	1000	<p>Possible values:</p> <ul style="list-style-type: none"> • 10 - Minimum • 5000 - Maximum
RTPMode	Yes	No	Enum	1	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
RTPProxyMode	Yes	No	Enum	1	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
RTPDirectMode	Yes	No	Enum	1	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
VideoProxyMode	Yes	No	Enum	1	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
VideoDirectMode	Yes	No	Enum	1	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue

MediaConfigID	Yes	No	int	1	Possible values: <ul style="list-style-type: none"> • 1 - Minimum • 65534 - Maximum
ToneTableID	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
ActionSetTableID	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
RouteTableID	Yes	Yes	int	1	Possible values: <ul style="list-style-type: none"> • 1 - Minimum • 65534 - Maximum
RingBack	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - sgrbpAuto • 1 - sgrbpAlways • 2 - sgrbpNever • 3 - sgrbpAutoOnAlertF • 4 - sgrbpAlwaysOnAle

HuntMethod	Yes	No	Enum	4	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - sghmStandard • 1 - sghmReverseSi • 2 - sghmRoundRot • 3 - sghmLeastIdle • 4 - sghmMostIdle • 5 - sghmOwnNumt
Direction	No	No	Enum	2	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - sgdirInbound • 1 - sgdirOutbound • 2 - sgdirBidirection:
PlayCongestionTone	No	No	Enum	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
Early183	No	No	Enum	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
AllowRefreshSDP	No	No	Enum	1	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
RTCPMultiplexing	No	No	Enum	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
OutboundProxy	No	No	string	none	256 - Max Length
ProxyIpVersion	Yes	No	Enum	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - eVersionPreferI • 1 - eVersionPreferI

OutboundProxyPort	No	No	int	5060	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
NoChannelAvailableId	No	No	int	34	Possible values: <ul style="list-style-type: none"> • 1 - Minimum • 127 - Maximum
TimerSanitySetup	No	No	int	180000	Possible values: <ul style="list-style-type: none"> • 180000 - Minimum • 750000 - Maximum
TimerCallProceeding	No	No	int	180000	Possible values: <ul style="list-style-type: none"> • 24000 - Minimum • 750000 - Maximum
ChallengeRequest	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
NotifyCACProfile	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
NonceLifetime	No	No	int	600	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 3600 - Maximum

Monitor	No	No	Enum	2	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - eProxyRegistrat • 1 - eProxyRegistration • 2 - eProxyRegistrat • 3 - eBasicCall
AuthorizationRealm	No	No	string	none	256 - Max Length
ProxyAuthorizationTableID	No	No	int	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
RegistrarID	No	No	int	0	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
RegistrarTTL	No	No	int	600	<p>Possible values:</p> <ul style="list-style-type: none"> • 60 - Minimum • 86400 - Maximum
OutboundRegistrarTTL	No	No	int	600	<p>Possible values:</p> <ul style="list-style-type: none"> • 60 - Minimum • 86400 - Maximum
DSCP	Yes	No	int	40	<p>Possible values:</p> <ul style="list-style-type: none"> • 0 - Minimum • 63 - Maximum

ListenPort_1	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
Protocol_1	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eTrNone • 1 - eTrUDP • 2 - eTrTCP • 3 - eTrTCP_UDP • 4 - eTrTLS • 5 - eTrTLS_UDP • 6 - eTrTLS_TCP • 7 - eTrTLS_TCP_L • 8 - eTrCount • 9 - eTrSCTP
TLSProfileID_1	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
LocalIP_1	No	No	string	none	50 - Max Length
ListenPort_2	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
Protocol_2	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eTrNone • 1 - eTrUDP • 2 - eTrTCP • 3 - eTrTCP_UDP • 4 - eTrTLS • 5 - eTrTLS_UDP • 6 - eTrTLS_TCP • 7 - eTrTLS_TCP_L • 8 - eTrCount • 9 - eTrSCTP
TLSProfileID_2	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
LocalIP_2	No	No	string	none	50 - Max Length

ListenPort_3	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
Protocol_3	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eTrNone • 1 - eTrUDP • 2 - eTrTCP • 3 - eTrTCP_UDP • 4 - eTrTLS • 5 - eTrTLS_UDP • 6 - eTrTLS_TCP • 7 - eTrTLS_TCP_L • 8 - eTrCount • 9 - eTrSCTP
TLSProfileID_3	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
LocalIP_3	No	No	string	none	50 - Max Length
ListenPort_4	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
Protocol_4	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eTrNone • 1 - eTrUDP • 2 - eTrTCP • 3 - eTrTCP_UDP • 4 - eTrTLS • 5 - eTrTLS_UDP • 6 - eTrTLS_TCP • 7 - eTrTLS_TCP_L • 8 - eTrCount • 9 - eTrSCTP
TLSProfileID_4	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
LocalIP_4	No	No	string	none	50 - Max Length

ListenPort_5	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
Protocol_5	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eTrNone • 1 - eTrUDP • 2 - eTrTCP • 3 - eTrTCP_UDP • 4 - eTrTLS • 5 - eTrTLS_UDP • 6 - eTrTLS_TCP • 7 - eTrTLS_TCP_L • 8 - eTrCount • 9 - eTrSCTP
TLSProfileID_5	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
LocalIP_5	No	No	string	none	50 - Max Length
ListenPort_6	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65535 - Maximum
Protocol_6	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eTrNone • 1 - eTrUDP • 2 - eTrTCP • 3 - eTrTCP_UDP • 4 - eTrTLS • 5 - eTrTLS_UDP • 6 - eTrTLS_TCP • 7 - eTrTLS_TCP_L • 8 - eTrCount • 9 - eTrSCTP
TLSProfileID_6	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
LocalIP_6	No	No	string	none	50 - Max Length
SIPtoQ850_TableID	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum

Q850toSIP_TableID	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
SipResponseCodes	Yes	Yes	string	408,409,411,413,500,501,503,504,580,604,606	200 - Max Length
NetInterfaceSignaling	Yes	No	string	none	64 - Max Length
NATTraversalType	Yes	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eNATTypeNone • 1 - eNATTypeStatic

NATPublicIPAddress	No	Yes	string	none	16 - Max Length
PassthruPeerSIPRespCode	No	No	Enum	1	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
SGLevelMOHService	No	Yes	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - mohDisable • 1 - mohEnable • 2 - mohEnableNoV
IngressSPRMessageTableList	No	No	string	none	60 - Max Length
EgressSPRMessageTableList	No	No	string	none	60 - Max Length
QoEReporting	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
VoiceQualityReporting	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue

RegisterKeepAlive	No	No	Enum	1	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
InteropMode	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eStandard • 1 - eBroadSoft • 2 - eO365 • 3 - eO365wAD • 4 - eHeaderTransp
AgentType	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - eBackToBackU • 1 - eAccessMode
RegistrantTTL	No	No	int	3600	Possible values: <ul style="list-style-type: none"> • 30 - Minimum • 86400 - Maximum
ADAttribute	No	No	string	pager	500 - Max Length
ADUpdateFrequency	No	No	string	1	100 - Max Length
ADFirstUpdateTime	No	No	string	00:00:00	500 - Max Length
Office365FQDN	No	No	string	none	1000 - Max Length
ICESupport	Yes	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
ICEMode	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - elceLite • 1 - elceFull

InboundNATTraversalDetection	Yes	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
InboundNATQualifiedPrefixesTableID	No	No	int	0	Possible values: <ul style="list-style-type: none"> • 0 - Minimum • 65534 - Maximum
InboundSecureNATMediaLatching	No	No	Enum	1	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
InboundSecureNATMediaPrefix	No	No	string	255.255.255.255	16 - Max Length
InboundNATPeerRegistrarMaxEnabled	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue
InboundNATPeerRegistrarMaxTTL	No	No	int	120	Possible values: <ul style="list-style-type: none"> • 30 - Minimum • 86400 - Maximum

RemoteHosts	Yes	No	string	none	2500 - Max Length
RemoteMasks	Yes	No	string	none	2500 - Max Length
SIPReSync	No	No	Enum	0	Possible values: <ul style="list-style-type: none"> • 0 - btFalse • 1 - btTrue



Helpful Tip

The POST can contain either only the attributes that are being updated, or the full set of attributes for the resource