

---

# GTT\_GTOPCSearch\_POST

---

## POST - GTOPCSearch

---

### REST API Method: POST

[/api/defGTT/GTTDatabase/\[string:aid\\_1\]/GTOPCSearches/GTOPCSearch](#)

Adds an GTOPCSearch managed object.

### URL:

[/api/defGTT/GTTDatabase/\[string:aid\\_1\]/GTOPCSearches/GTOPCSearch](#)

### HTTP Method:

POST

### Requires Authentication:

true

### Description:

Parameter	Description
[string:aid_1]	[GTTDatabase/Type]
Payload(Not necessarily in order)	{"EPR": "value", "OPCRange": "value", "DBDefName": "value", "PCListName": "value", "Description": "value"}

### Parameters:

Parameter Name	Required	Create	Read-Only	Data Type	Description
EPR	Yes	Yes	Yes	string	GT OPC Search Entry Point Reference (EPR). TL1Name: EPR
OPCRange	Yes	Yes	Yes	string	OPC Range (wildcard and range supported). TL1Name: OPC_RANGE
DBDefName	Yes	Yes	Yes	string	GTT Database Definition Name. TL1Name: DB_DEF_NM
PCListName	No	Yes	No	string	Name of Point Code List to which the SS7 messages will be sent. TL1Name: PC_LIST_NAME
Description	No	Yes	No	string	Description for the given GT OPC Search Record TL1Name: DESC