

---

# GTT\_PCListRecord\_PUT

---

## PUT - PCListRecord

---

### REST API Method: PUT

[/api/defGTT/GTTDatabase/\[string:aid\\_1\]/PCLists/PCList/\[string:aid\\_2\]/PCListRecord/\[string:aid\\_3\]](#)

Modifies an PCListRecord managed object.

### URL:

[/api/defGTT/GTTDatabase/\[string:aid\\_1\]/PCLists/PCList/\[string:aid\\_2\]/PCListRecord/\[string:aid\\_3\]](#)

### HTTP Method:

PUT

### Requires Authentication:

true

### Description:

| Parameter                         | Description   |
|-----------------------------------|---|
| [string:aid_1]                    | [GTTDatabase/Type]  |
| [string:aid_2]                    | [PCList/Type]   |
| [string:aid_3]                    | [PCListRecord/PointCode],[PCListRecord/NetworkAppearance],[PCListRecord/Cost],[PCListRecord/Weight] |
| Payload(Not necessarily in order) | {"PointCode":"value", "NetworkAppearance":"value", "Cost":"value", "Weight":"value"}                |

### Parameters:

| Parameter Name    | Required | Create | Read-Only | Data Type    | Description  |
|-------------------|----------|--------|-----------|--------------|--|
| PointCode         | Yes      | Yes    | Yes       | string       | Destination Point Code. TL1Name: PC  |
| NetworkAppearance | Yes      | Yes    | No        | PCListRecNA  | NA associated with this PC in the given list [PC LIST VALUE (0, 1 to 255)] TL1Name: NA |
| Cost              | No       | Yes    | No        | int32        | Cost associated with this point code in the given list [0..255]. TL1Name: COST         |
| Weight            | No       | No     | No        | Weight1to100 | Weight associated with this point code in the given list [1 to 100] TL1Name: WEIGHT    |