

GTT_GTCalledSearch_POST

POST - GTCalledSearch

REST API Method: POST

[/api/defGTT/GTTDatabase/\[string:aid_1\]/GTCalledSearches/GTCalledSearch](#)

Adds an GTCalledSearch managed object.

URL:

[/api/defGTT/GTTDatabase/\[string:aid_1\]/GTCalledSearches/GTCalledSearch](#)

HTTP Method:

POST

Requires Authentication:

true

Description:

Parameter	Description
[string:aid_1]	[GTTDatabase/Type]
Payload(Not necessarily in order)	{"MinimumDigits":"value", "MaximumDigits":"value", "GTI":"value", "NP":"value", "TT":"value", "NAI":"value", "GTCallingSearchesEPR":"value", "DBDefName":"value", "SSN":"value", "PCListName":"value", "GTModificationName":"value", "Description":"value"}

Parameters:

Parameter Name	Required	Create	Read-Only	Data Type	Description
MinimumDigits	Yes	Yes	Yes	string	GT Digits Range minimum (GTAI). TL1Name: MIN_DIGITS
MaximumDigits	Yes	Yes	Yes	string	GT Digits Range maximum (GTAI). TL1Name: MAX_DIGITS
GTI	Yes	Yes	No	GtiAny	Global Title Indicator (0000/0001/0010/0011/0100/ANY). TL1Name: GTI
NP	Yes	Yes	No	NumberingPlanAny	Numbering Plan ([0..15] or ANY). TL1Name: NP
TT	Yes	Yes	No	Any_256	Translation Type ([0..255] or ANY). TL1Name: TT
NAI	Yes	Yes	No	Any_128	Nature of Address Indicator ([0..127] or ANY). TL1Name: NAI
GTCallingSearchesEPR	Yes	Yes	No	string	GT Calling Searches EPR for advanced search via Calling Party Address. TL1Name: CLG_EPR

DBDefName	Yes	Yes	Yes	string	GTT Database Definition Name. TL1Name: DB_DEF_NM
SSN	Yes	Yes	No	SSNAny	Subsystem Number ([0..255], NOT PRESENT, or ANY). TL1Name: SSN
PCListName	No	Yes	No	string	Name of Point Code List to which the SS7 messages will be sent. TL1Name: PC_LIST_NAME
GTModificationName	No	Yes	No	string	Name of GT Modification or NONE. TL1Name: GT_MODIF_NAME
Description	No	Yes	No	string	Description for the given GT Called Search TL1Name: DESC